

Apeos C325 z / C325 dw  
ApeosPrint C325 dw



# Amazingly Compact



## Amazingly Compact Yet Reliable

- Machine life up to 100,000 pages
- Maximized reliability with less mechanical parts

## Superb Printing Quality

- Caters to a wide printing needs from office to stores
- Rich colour expression with LED printhead and IReCT\*
- EA-Eco toner for fine text and fine lines
- Image enhancement technology reproduces smooth diagonal lines

\* Image Registration Control Technology



Compact Size  
by **40%**

## Security for Important Information

- Prevents information leakage with Secure Print
- SMBv3 / TLS1.3 supported for secure communication
- Connect to wireless LAN with WPA-Enterprise
- Password protection for incoming fax
- Re-enter fax number to prevent fax transmission error

# Apeos C325 z / C325 dw and ApeosPrint C325 dw superb colour & monochrome printing quality,

## Truly Powerful

Fits anywhere, for counter services, clinics and more

- Compact design
- Fast printing : 31 ppm on A4 size, 41 ppm on A5 size
- 1-pass, 2-sided scanning : 45 ppm on B/W, 22 ppm on colour
- Handle high-volume documents with Automatic document Feeder
- High-yield toner cartridges
- Scan files to your PC, USB flash drive, E-mail, and shared folders
- ID card scan
- Cost & paper saving with automatic 2-sided printing
- Security control by disabling Wi-Fi / NFC connection at the counter services or public spaces

### Apeos C325 z / C325 dw

- A4 all-in-one printer
- 2.8-inch colour touch panel
- Ethernet, USB & Wi-Fi supported
- 1 pass, 2 sided scanning Duplex Automatic Document Feeder\*
- Scan to PC, email, shared folders
- ID card copy, 2-up copy & printing



Print Copy Fax\* Scan

\* Available only for Apeos C325 z

Apeos C325 z / C325 dw **21kg**



W410 x D430 x H366 mm

ApeosPrint C325 dw **17kg**



W410 x D430 x H255 mm

### ApeosPrint C325 dw

- A4 printer
- 2-line LCD display
- Ethernet, USB & Wi-Fi supported



Print



Print Utility



# Seamless Connectivity

Seamless connectivity with mobile devices for Copy, Fax, Print, Scan\*<sup>1</sup> jobs using the Print Utility\*<sup>2</sup> application.

- Mobile device can be used as an alternative UI for operations control to minimise common touch points
- Frequent settings can be saved as "Favorites"
- Directly send fax or email with the addresses stored in the smartphone

Note: Connect to machine via wireless environment or Wi-Fi direct connection.

\*1: Scan to Mobile, E-mail.


\*2: It can be downloaded free of charge from Google Play™ or App Store.



# Manage & Control

Easy installation and easy fleet management for retail stores & enterprise offices

- Hassle-free for multiple manual settings. Setting cloning available for multiple-device installation.
- Save your time with SMTP server detection in "scan to mail", "fax to mail" setting.



- Suitable for shop business with flexible access setting\*

\* Available only for Apeos C325 z / C325 dw. Fax is available only for Apeos C325 z

|                   | Store Manager | Full-time Worker | Part-time Worker |
|-------------------|---------------|------------------|------------------|
| Device Management | ●             | -                | -                |
| Scan              | ●             | ●                | ●                |
| E-Mail            | ●             | ●                | -                |
| USB Direct Print  | ●             | ●                | ●                |
| Fax               | ●             | ●                | -                |

cater to your needs with amazing compactness, high reliability and security.

# Smart & Scalable

- 1. Automatic Document Feeder:**  
Scans sheet documents continuously
- 2. 2.8-inch colour touch panel:**  
Intuitive colour touch panel lets you find just what you want at a glance
- 3. USB port:**  
Use your own USB flash drive to print / scan to directly
- 4. Bypass Tray (50 Sheets):**  
Can feed various paper types such as envelopes and postcards
- 5. Standard Tray (250 sheets):**  
Supports various types & sizes of paper
- 6. Optional Tray (250 sheets):**  
Maximum 550 sheets paper capacity. Scalable for high-volume printing needs
- 7. Built-in NFC:**  
Start Print Utility application and place your mobile device over the NFC tag to print / scan
- 8. Wi-Fi Direct:**  
Offers built-in wireless printing function



2.8-inch colour touch panel



## Options

|                        |  |
|------------------------|--|
| Product Name           |  |
| 250 Sheets Feeder Unit |  |

## Consumables/Supplies

| Product Name                          | Yield                            |
|---------------------------------------|----------------------------------|
| Drum Cartridge (YMCK)                 | Up to 50,000 pages* <sup>1</sup> |
| High Capacity Toner Cartridge (K)     | Up to 6,000 pages* <sup>2</sup>  |
| High Capacity Toner Cartridge (C)     | Up to 4,000 pages* <sup>2</sup>  |
| High Capacity Toner Cartridge (M)     | Up to 4,000 pages* <sup>2</sup>  |
| High Capacity Toner Cartridge (Y)     | Up to 4,000 pages* <sup>2</sup>  |
| Standard Capacity Toner Cartridge (K) | Up to 3,000 pages* <sup>2</sup>  |
| Standard Capacity Toner Cartridge (C) | Up to 2,000 pages* <sup>2</sup>  |
| Standard Capacity Toner Cartridge (M) | Up to 2,000 pages* <sup>2</sup>  |
| Standard Capacity Toner Cartridge (Y) | Up to 2,000 pages* <sup>2</sup>  |
| Waste Toner Bottle                    | Up to 6,000 pages* <sup>1</sup>  |

\*1: The number of printable pages is a reference value derived from the average of 3 sheets printed in A4, 1 sided, image coverage per colour 5 %, colour/monochrome rate 50: 50 in one setting, under continuous printing usage conditions. The actual number of printable pages may vary to below half the reference value, depending on paper type, paper direction, input/output tray settings, initialization operations upon powering ON/OFF the device, tuning operations to maintain print quality, and other such usage environment conditions. \*2: Published value based on ISO/IEC 19798 standards. The actual number of printable pages may vary significantly from the published value, depending on printing content, paper size, paper type, usage conditions, initialization operations upon powering ON/OFF the device, tuning operations to maintain print quality, and other such usage environment conditions.

# Apeos C325 z / C325 dw and ApeosPrint C325 dw, Functions & Specifications

For the printing function of Apeos C325 z / C325 dw, please refer to the "Print Function" of ApeosPrint C325 dw below:

## Basic Specifications / Copy Function

| Item  | Apeos C325 z  | Apeos C325 dw                                    |
|---|---|--|
| Type  | Desktop   |  |
| Memory Capacity                                 | 512 MB (Max: 512 MB)  |  |
| Storage Device Capacity                         | -   |  |
| Colour Capability                               | Full Colour   |  |
| Scan Resolution                                 | 600 x 600 dpi   |  |
| Printing Resolution                             | 600 x 2,400 dpi   |  |
| Warm-up Time*1                                  | 35 seconds or less (23 degrees Celsius room temperature)        |  |
| Recovery Time (Recovery Time from Sleep Mode)*1 | 17 seconds or less (23 degrees Celsius room temperature)        |  |
| Original Size                                   | Maximum of A4, Letter, Legal*2 for both Sheet and Book          |  |
| Paper Size                                      | Max   | A4, Letter, Legal                                |
|   | Min   | A6, 76 x 127 mm                                  |
| Image loss width                                | Lead edge 4.1 mm, Trail edge 4.1 mm, Right/Left edge 4.1 mm     |  |
| Paper Weight*3                                  | Paper Tray  | 60 to 176 gsm                                    |
|   | Bypass Tray   | 60 to 176 gsm                                    |
| First Copy Output Time*4                        | B/W: 9.5 sec. (A4) Colour: 12.0 sec. (A4)                       |  |
| Continuous Copy Speed*5                         | A4  | B/W: 31 ppm Colour: 31 ppm                       |
|   | A5  | B/W: 41 ppm Colour: 41 ppm                       |
| Paper Tray Capacity*6                           | Standard  | Standard Tray: 250 sheets Bypass Tray: 50 sheets |
|   | Optional  | 250 Sheets Feeder Unit: 250 sheets               |
|   | Max   | 550 sheets [Standard + 250 Sheets Feeder Unit]   |
| Output Tray Capacity*6                          | 150 sheets (Face down)  |  |
| Power Supply                                    | AC220-240 V +/- 10%, 10 A, 50/60 Hz common                      |  |
| Maximum Power Consumption                       | 1,120 W Sleep Mode: 0.5 W Low Power Mode: 11 W Ready Mode: 41 W |  |
| Dimensions                                      | W 410 x D 430 x H 366 mm  |  |
| Weight*7  | 20.6 kg   | 20.5 kg  |

\*1: Measurements based on our standards. It takes more time depending on the usage conditions and image quality control. \*2: Not available on Scanner Glass. \*3: It is recommended to use our recommended paper. Correct print output may not be possible depending on the requirement. \*4: Measured in accordance to ISO/IEC 29183. \*5: The speed may be reduced due to the image quality adjustment. \*6: 80 gsm paper. \*7: Excluding Toner Cartridge.

## Scan Function

| Item            | Description  |
|-----------------|--|
| Type            | Colour Scanner   |
| Scan Resolution | Scan to PC<br>TWAIN: 50 x 50 to 9,600 x 9,600 dpi<br>WIA: 75 dpi, 100 dpi, 150 dpi, 200 dpi, 300 dpi, 400 dpi, 600 dpi |
|                 | Scan to Network / e-mail<br>200 dpi, 300 dpi, 400 dpi*1, 600 dpi*1   |
| Scan Speed      | Same as the Scan Speed for the Automatic Document Feeder   |
| Interface       | Standard<br>Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T, USB2.0 Wireless LAN (IEEE 802.11 b / g / n)                   |

Note: WIA stands for Windows Image Acquisition. \*1: When scanner glass is used.

## Fax Function

| Item                 | Description  |
|----------------------|--|
| Original Size        | Scanner Glass: Max A4, Letter Automatic Document Feeder: Max Legal |
| Recording Paper Size | Max: Legal; Min: A4, Letter  |
| Transmission Time    | 3 seconds and more but fewer than 4 seconds*1                      |
| Transmission Mode    | ITU-T G3   |
| Applicable Lines     | Telephone subscriber line, PBX, Maximum 1 port*2 (G3-1 port)       |

Note: Fax function is available only for Apeos C325 z. \*1: When A4 size document with approximately 700 characters is transmitted in standard image quality (8 x 3.85 lines/mm) and in high-speed mode (33.6 kbps or faster, JBIG). Only indicates the time for transmitting the image information and does not include the communication control time. The total communication time will vary depending on the document, the type of machine receiving the fax, and line condition. \*2: No. of FAX lines is up to 1 port. Port refers to number of channels for FAX.

## Automatic Document Feeder

| Item                         | Apeos C325 z   | Apeos C325 dw   |
|------------------------------|--|---|
| Type                         | 1 pass, 2 sided scanning Duplex Automatic Document Feeder            | Automatic Document Feeder                                     |
| Original Size / Paper Weight | Max: Legal; Min: A5*1<br>60 to 105 gsm (In Duplex:<br>60 to 105 gsm) | Max: Legal; Min: A5*1<br>60 to 105 gsm                        |
| Capacity*2                   | 50 sheets  |   |
|                              | Copy (A4, Simplex)<br>B/W: 30 ppm Colour: 16 ppm                     |   |
| Scan Speed*3                 | B/W: 30 ppm, Colour:<br>15 ppm                                       |   |
|                              | Scan*4   | (1 pass, 2 sided scanning;<br>B/W: 45 ppm, Colour:<br>22 ppm) |
|                              |  | B/W: 30 ppm, Colour:<br>15 ppm                                |

\*1: The minimum custom size is 139.7 x 139.7 mm. \*2: 80 gsm paper. \*3: The scanning speed varies depending on the documents. \*4: Standard document (A4), 200 dpi, to USB flash drive.

## Print Function

| Item                         | ApeosPrint C325 dw   |   |
|------------------------------|--|---|
| Printing Method              | LED Electrophotography   |   |
| Warm-up Time*1               | 35 seconds or less (23 degrees Celsius room temperature).<br>17 seconds or less from Sleep Mode. |   |
| Continuous Print Speed*2     | Simplex  | A4 Colour: 31 ppm, B/W: 31 ppm A5 Colour: 41 ppm, B/W: 41 ppm   |
|                              | Duplex   | A4 Colour: 19 ppm, B/W: 19 ppm A5 Colour: 23 ppm, B/W: 23 ppm   |
| First Print Output Time*3    | Colour: 11.0 seconds (A4), B/W: 10.0 seconds (A4)  |   |
| Printing Resolution          | Standard   | [PCL Driver] 600 x 2,400 dpi  |
|                              | Standard Tray  | [PostScript language compatible Driver] 600 x 2,400 dpi   |
| Paper Size                   | Standard Tray  | A6, A5, JIS B5, A4, Letter, Executive (184 x 267 mm), Folio (216 x 330 mm), Legal, COM-10, Monarch, DL, C5, Postcard (4 x 6"), Postcard (5 x 7"), Custom Size (Width: 76.2 to 215.9 mm, Length: 127.0 to 355.6 mm)        |
|                              | Bypass Tray  | A6, A5, JIS B5, A4, Letter, Executive (184 x 267 mm), Folio (216 x 330 mm), Legal, COM-10, Monarch, DL, C5, Postcard (4 x 6"), Postcard (5 x 7"), Custom Size (Width: 76.2 to 215.9 mm, Length: 127.0 to 355.6 mm)        |
|                              | Optional Tray  | 250 Sheets Feeder Unit: A5, JIS B5, A4, Letter, Executive (184 x 267 mm), Folio (216 x 330 mm), Legal, Custom Size (Width: 76.2 to 215.9 mm, Length: 210.0 to 355.6 mm)   |
| Paper Weight*4               | 2 Sided Printing   | A5, JIS B5, A4, Letter, Executive (184 x 267 mm), Folio (216 x 330 mm), Legal, Custom Size (Width: 139.0 to 215.9 mm, Length: 210.0 to 355.6 mm)  |
|                              | Standard Tray  | 60 to 176 gsm   |
| Paper Tray Capacity*5        | Bypass Tray  | 60 to 176 gsm   |
|                              | Optional Tray  | 250 Sheets Feeder Unit: 60 to 176 gsm   |
| Supported Operating System*6 | Standard   | Standard Tray: 250 sheets Bypass Tray: 50 sheets<br>Optional Tray: 250 Sheets Feeder Unit: 250 sheets<br>Max: 550 sheets [Standard + 250 Sheets Feeder Unit]  |
|                              | 2 Sided Printing   | 60 to 176 gsm   |
| Output Tray Capacity*5       | 150 sheets (Face down)   |   |
| CPU                          | ARM Single core 667 MHz  |   |
| Memory Capacity              | 512 MB (Max: 512 MB)   |   |
| Storage Device Capacity      | -  |   |
| Page Description Language    | Standard   | PCL5 / PCL6, PostScript language compatibility  |
| Interface                    | Standard   | [PCL Driver]<br>Windows 11 (64 bit) Windows 10 (32 bit/64 bit)<br>Windows Server 2022 (64 bit) Windows Server 2019 (64 bit)<br>Windows Server 2016 (64 bit)   |
|                              | Standard   | [PostScript language compatible Driver]<br>Windows 11 (64 bit) Windows 10 (32 bit/64 bit)<br>Windows Server 2022 (64 bit) Windows Server 2019 (64 bit)<br>Windows Server 2016 (64 bit)<br>macOS 14 / 13 / 12 / 11 / 10.15 |
| Network Protocol             | TCP/IP (lpd, IPP/PPS, Port9100, WSD)   |   |
| Power Supply*7               | AC220-240 V +/- 10%, 10 A, 50/60 Hz common   |   |
| Operating Noise*8            | In Operation: 6.99 B, 50.7 dB (A) Ready Mode: Noise-free   |   |
| Maximum Power Consumption    | Max  | 1,110 W   |
| Average                      | Ready Mode: 37 W In Operation: 407 W Sleep Mode: 0.5 W   |   |
| Dimensions                   | W 410 x D 430 x H 255 mm   |   |
| Weight                       | 17.4 kg (Including consumables and drum)   |   |
|                              | 14.2 kg (Excluding consumables and drum)   |   |

Note: WSD stands for Web Services on Devices.

\*1: Measurements based on our standards. It takes more time depending on the usage conditions and image quality control. \*2: When continuously printing original(Plain). The performance may be reduced depending on the paper type and the paper size. The speed may be reduced due to the image quality adjustment. Measured in accordance to ISO/IEC 24734. \*3: When feeding from feeder tray of machine and USB connection. Numeric value varies depending on output environment. Measured in accordance to ISO/IEC 17629. \*4: It is recommended to use our recommended paper. Correct print output may not be possible depending on the requirement. \*5: 80 gsm paper. \*6: Please refer to our official website for the latest supported OS. \*7: Power outlets that provide the above power level is recommended. Maximum machine measured current: 6 A. \*8: Measured in accordance to ISO7779. Unit B: Sound Power Level LWAd. Unit dB: Radiated Sound Pressure Level LpAm (bystander position). "Noise-free" refers to Radiated Sound Pressure Levels equal to or below ISO 7779 background noise absolute standards for each bystander position.

### Notes

- To comply with paper weight specifications, it is recommended to use our recommended paper. Document may not be printed correctly depending on usage conditions.
- Functional spare parts will be available for at least 7 years after the product is no longer manufactured.

# FUJIFILM

## Manufacturer

### FUJIFILM Business Innovation Corp.

#### Headquarters

9-7-3, Akasaka Minato-ku, Tokyo 107-0052

TEL: +81-3-6271-5111

[fujifilm.com/fbglobal](http://fujifilm.com/fbglobal)

The available model varies depending on the country/region. Please ask the sales representatives for details.

The product specifications, appearance and other details in this brochure are subject to change without notice for improvements.

**Reproduction Prohibitions** Please note that reproduction of the following is prohibited by law: •Domestic and foreign currencies, government-issued securities, and national bonds and local bond certificates. •Unused postage stamps, post cards, etc. •Certificate stamps stipulated by law. •Reproducing works forming the subject matter of copyright (literary works, musical works, paintings, engravings, maps, cinematographic works, drawings, photographic works, etc.) is not permitted unless the reproduction is for the purpose of personal use, family use or other similar uses within a limited circle.

**Trademarks** •FUJIFILM and FUJIFILM logo are registered trademarks or trademarks of FUJIFILM Corporation. •Apeos is registered trademark or trademark of FUJIFILM Business Innovation Corp. •Adobe, Adobe logo, PostScript and PostScript logo are either registered trademarks or trademarks of Adobe in the United States and/or other countries. •Apple, Mac, macOS, OS X and AirPrint are trademarks of Apple Inc. registered in the U.S. and other countries and regions. •Mopria, the Mopria Logo, and the Mopria Alliance word mark and logo are registered and/or unregistered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. •All product names and company names mentioned in this brochure are trademarks or registered trademarks of their respective companies.



### For Your Safety

Before using the product, read the Instruction Manual carefully for proper use. Use the product with the power source and voltage specified. Be sure to establish ground connection. Otherwise, electronic shock may result in the case of a failure or short circuit.